

## Anti-stick stripping aid

## RT-3140

## Features and advantages:

The low surface tension of this product can improve the smooth surface of the coating and improve the wettability of the substrate. It can effectively improve the leveling and surface smoothness of the coating, improve the anti-scratch and anti-adhesion, and prevent shrinkage, floating color and flaring. In the field of application of water transfer removable film, the addition amount is small, yellowing resistance, excellent compatibility, does not affect the drying speed of the coating and the toughness of the coating after film formation.

1. the deep fine grain release paper can enhance the permeability, increase the three-dimensional sense of grain, soft luster, and dry wax feeling without greasy, wet smooth, spread with good.

2. improve the peeling force of the tear coating effect is significant.

3, easy to precipitate, resistant to yellowing.

4. It can effectively prevent the occurrence of watermarks, water strips, water spots, drag lines, oil spots and other ills in production.

## Product specification:

	appearance	Light brown transparent liquid	
Tianjin Ruike Chemical Co. LTD Tel:+86 18526852692			
Add:Room 116-11, 160 Xiangyuan Road, Jingjin Science and Technology Valley Industrial Park, Wuqing			
District, Tianjin			
tjr	khg@126.com	www.rk-chem.com	



Active ingredient	100%
Viscosity (25°C, mPa.S)	800-1800.
Surface tension (mN/m, $25^{\circ}$ C)	25 or less
ingredient	Modified organosilicon
	compounds

Application: acrylic, polyurethane, nitro system

Recommended dosage: 0.5-3% of the total formula

**Usage:** Add the curing agent before adding, adding method without special requirements, fully stir evenly.

Packing: Net weight 25Kg/ barrel, 200kg/ barrel.